

## **TOYOTA MOTOR CORPORATION**

EXECUTIVE ORDER A-014-0547 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODI YEA	R	TEST GROUP			M	VEHICLE TYPE C=passenger car; LDT=light-di DV=medium-duty vehicle; LVW vehicle weight; ALVW=adjuster	V=loaded d LVW)	STAN (LEV=low transition	HAUST EMISSION IDARD CATEGORY remission vehicle; TLE nal LEV; ULEV=ultra LE JLEV=super ULEV)	V⇒	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
2000	2006 6TYXT04.7PKW			W	0	LDT: 6001-8500# GVV ver 3750# LVW, 5751-8500	N, #ALVW		TEA II OFEA		120K / 150K	Gasoline			
No.	FAMIL	LY (E	VAF)	<u>'</u>	lo.	SPECIAL FEA EMISSION CONTROL	TURES &	(ECS)	OC	/TWC=oxidizing/3-way	cat. ADSTWC=adsorbing TWC				
1	6TYXR0190P32				1	2WU-TWC, 2TWC,	2HAFS, 2F	IO2S, SFI.	HALL	O/MAPO≃air-fuel ratio se	O2S=oxygen sensor/heated O2S ensor/heated AFS EGR=exhaust				
2		•			2		*		⊣  gas recirculation_AIR/PAIR≃secondary air injection/pulse						
3		*			3	<del></del>	•	<del></del>	TBI= throttle body injection TC/SC=turbo /super charger						
4		* :		1	4	**	•			CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
EVAF No.	EC No		ENGIN SIZE (			VEHICLE MAKES & MODELS			ECT TO SFTP E UNDERLINED	11					
1	1		4.7			TOYOTA: TUNDRA 2WD/4WD, SEQUOIA 2WD/4WD									
	*	*													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NM AVE	NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF = * CH4 RAF = *											carbons Co			
CER	T	STD	CERT CERT		NMHC	mg=mill	gram m	- [B,]-11	unning lo: =1000 mil	33 UN	CALC TRIVE	jalion oli	pensed] renhelt	tivity adjust =on-board re SFTP=supj	stueling vac	or recover	/ g=gram	
0.04	7   1	0.062				[g/ml]	CERT	(g/mi) STD		Ox [g/m	i]		HO [mg	/mi]	PM [g	/mi]	Hwy NC	x [g/mi]
- 15	STATE OF EAL				<del></del>	<del> </del> -			CER				(1	STD	CERT	STD	CERT	STD
	@ 50K					0.040	0.3	1.7	0.02	2 0	.05			В	*		0.01	0.07
	@∪		0.03	5	•	0.055	0.3	2.1	0.03	3 0	0.07 +			11	*	*	0.01	0.09
7	@ 50	°F & 4K	*		*	*	•	•	*	ļ	*	•		*	*	•	*	*
@ 20	CO [g/mi]   SFTP 1 = @ 4K (SULEV, ULEV,				(composite) (com			g/mi] NMHC+N posite) [g/mi] [US				NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]				
<b></b>			- ( <u>u</u> g UL	(1161 I,	ILEV)	CERT	STD	CERT	STD	CERT	r   s	TD	CERT	STE	CERT	STD	CERT	STD
CERT	2.1				SFTP 1	*	*	-	*	0.01	0	.60	3.5	11.8	0.03	0.44	0.4	4.0
STD	12.5	3.4			SFTP 2	*	*	1	*	*	_	*	*	*	+	•	•	+
@ UL		EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EVAPOR					ATIVE	FAMI	Y 3	FV	EVAPORATIVE FAMILY 4			
	3-D	2-D	· [ ]	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-		RL	ORVR		2-D	RL	ORVR
CERT	0.36	0.36	i 0.	.004	0.03	*	*	*	*		+	<del>-</del> +	*	*	, J-D	<del>2-D</del>	KL.	UKVK
STD	0.90	1.15	5 0	0.05	0.20	*	*	*		*	*		*	<del></del> -	*		*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to 13 CCR Section 1961(a)(10).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of July 2005.

Replace Suspoint

Mobile Source Operations Division