

#### DAIMLERCHRYSLER AG

**EXECUTIVE ORDER A-003-0326** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP	VEHICLE TYPE	EXHAUST EM STANDARD CA		USEFU (mil		IN COM ("=N/A o A/E=e	MEDIATE  J-USE PLIANCE or ful! In-use; xh. / evap. diate in-use)	FUEL TYPE
2007	7MBXV03.0U2A	Passenger Car	"LEV II" Ultra Low Emission Vehicle (LEV II ULEV)		EXH / ORVR 120K	ORVR EVAP		EVAP *	Gasoline (Tier 2 Unleaded)
No.	ECS & S	EVA	PORATIVE I	FAMILY (EV	AF)		DISPLAC	EMENT (L)	
1	2TWC, 2HO2S(2), SFI, AIR, OBD(P)								
*	*					3			
*			74 75						3
*		*	124 124				Ş		

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50<sup>0</sup> Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).


Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles



### **ATTACHMENT**

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG	ELECT I	MMOC	2.045.4									VII gasuin		
AVERAG			@ RAF=* RAF = *	NMOG or	HCHO=form	ane; NMQG= naldehyde; P	non-CH4 org	anic gas; NA	AHC=non-CH	4 hydrocarbi	on; CO=carbo	in monoxide; f /test]≃2/3 day	Ox=oxides o	if nitragen;
CERT	STD	NMOG	NMHC	NMHC STD	hot-soak; R	L (g/m/)=runi =1000 miles:	ning loss: OF	VR (g/gallon	dispensed]=	on-board ref	ueling vapor i al test procedi	/test] <b>≃2/3</b> day fec <b>overy; g</b> =gr	diumal+ am; <b>mg</b> ≃milli	gram
0.039	0.043	CERT (g/mi)	CERT [g/mi]	[g/mi]		g/mi]	NOx	[g/mi]	HCHO	mental federa [ <mark>mg/</mark> mi]	il test procedi	g/mi]		ox [g/mi]
	@ 50K	0.040				STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
		0.012		0.040	0.2	1.7	0.02	0.05	0.2	В.	*	*	0.001	0.07
	@ UL	0.026	*	0.055	0.3	2.1	0.02	0.07	0.4	11.	•		0.001	0.09
62 A.	50°F & 4K	*	*	*	*	*	4	*	*	*	•			*

	O [g/mi] 20°F & 50K			Ox [g/mi] oosite)		g/mi] posite)		C+NOx [US06]		[g/mi] 306]		S+NOx [SC03]	co	[g/mi] 2031
		<u> </u>	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	2.4	SFTP @ 4000 miles	*	*	*	-	0.04	0.14	1.3	8.0	0.03	0.20	0,5	2.7
STD	10.0	SFTP @ * miles	*	*	*	*	*	•	-	*	-	*	*	*

Evaporative Family		al + Hot Soak est) @ UL		nal + Hot Soak test) @ UL		ig Loss iile) @ UL	On-Board Ref Recovery (gram	ueling Vapor s/gallon) @ ป
	CERT	STD	CERT	STD	CERT	STD	CERT	STD
7MBXR0155LNC	0.44	0.50	0.39	0,65	0.000	0.05	0.004	
7MBXR0155LNS	0.30	0.50	0.39	0.65	0.000	0.05		0.20
*	*	*	*	•		1	0.004	0.20
*	*	sk	*		,		*	*

<sup>\*=</sup> not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=toaded vehicle weight; ALVW=adjusted LVW; LEV=iow emission vehicle; TLEV=transitional LEV; ULEV=ulra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; OZS=oxygen sensor; HO2S=heated OZS, AFS/HAFS=air- fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; DGI=direct gasoline fuel injection; TC/SC= utrob/super charger; CAC=charge air cooler, OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=ilquefied petroleum gas; E85="85%" Ethanol Fuel;

## 2007 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E≃exi	MEDIATE USE LIANCE full in-use; n. / evap. ate in-use)  EVAP	PHASE-IN STD.	II dao
MERCEDES-BENZ	C280	7MBXR0155LNC	1	3	*	*	SFTP	Partial
MERCEDES-BENZ	SLK 280	7MBXR0155LNS	1	3	*	+	SFTP	Partial