

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

							EYHA	IST EMISSION	EXHAUST & ORVR	FUEL TYPE				
MODE		TEST GROUP			VEHICLE TYPE =passenger car; LDT=light-duty V=medium-duty vehicle; LVW=l vehicle weight; GVW=gross ∨	STAND/ (LEV=low er transitional	ARD CATEGORY hission vehicle; TLEV: LEV: ULEV=ultra LEV; V=super ULEV)	/ EVAPORATIVE	(CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas					
2007	7	7GMXT03.9140		LD	T: <6000# GVW, 3751-57501	U	SEPA Bin 5 s ARB "LEV II" LE\	120K / 150K	Flexible Fuel: Ethanol (E85) / Gasoline (Tier 2 Unleaded)					
	FV/	APORA	TIVE 2	<u> </u>	SPECIAL FEAT	TURES	8.	* = not applicable		cat. ADSTWC=adsorbing TWC D2S=oxygen sensor/heated O2S				
No.	Io. FAMILY (EVAF)				EMISSION CONTROL			MACCALACS=sir_fuel ratio s	ansormeated AFS CUR-exitava					
1		MXR017		1	SFI,T\	NC HO2	S(2),OBD (F)	like MERCEL weithood	gas recirculation AIRPAIR=secondary air injection/pulse AIR MFI/SFI= multiport fuel injection/sequential MFI					
<u>.</u>		MXR0203958 2						TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-boar diagnostic prefix 2=parallel (2) suffix=series						
2	761	1WAR0203530 2												
3								<u> </u>						
EVAI	• ;	ECS ENGINE No. SIZE (L)			VEHICLE MAKES & MODELS	NDARDS AF	JECT TO SFTP RE <u>UNDERLINED</u>	ABBREVIATIONS:						
		Chevrolet Uplander FV						inder FWD, Pontiac	ntiac Montana SV6 FWD					
1_	—.↓		3.9		Chevrolet Uplander FWD, Pontiac Montana SV6 FWD , Buick Terraza FWD, Saturn Relay FWD									
2	İ	1]	3.9	Щ	Cuevrolet Opi	alluci I	77D, 1 0171140							
•		*	•	1										

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF = * (*); CH4 RAF = *		NMOG or NMHC	of nitroger	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen HCHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2/3 D [g/rest]=2/3 day diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refuelling vapor recovery g=gram mg=milling m mi=mile K=1000 miles F=degrees Fahrenhelt SFTP≃supplemental federal test procedure											
CERT	r STD		NMOG	NMHC	STD [g/ml]	triB-immilian im same			Ox [g/ml]		HCHO [mg/mi]		PM (g/mi)		ni]	Hwy NOx [g/mi]		
0.054	0.054 0.055		CERT (g/mi)	[g/mi]		CERT	STD	CERT			ERT			RT	STD	CERT	STD	
Galletin I.	@ 50K		0.056	· ia	0.075	1.1	3.4	0.04	0.05	- 1	1			•		(0.03)	(0.07)	
ta ta			$\{0.032\}$		(0.075)	(1.7)	(3.4)	(0.03)			<u>() </u>					0.04	0.09	
	@ UL		0.061	•	0.090 (0.090)	1.3 (1.9)	(4.2)	(0.05)	0.07		(,	(18)		*		(0.05)	(0.09)	
	and the second		(0.036)	 	10.0307	1.15,	1,,,,,,	 	+		*	•	•		•	*	. •	
200 Car 100 Car	CO [a/mi] SFTP 1 = @ 4K (SULEV, ULEV,				NMHC+NOx [g/mi] (composite)		CO [g/mi] (composite)		NMHC+NOx [g/ml] [US06]			CO [g/mi] (US06)		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
@ 20°	F8	L	EV) or 50K	(Tier 1, TLEV) ier 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE		TD	CERT	STD	CERT	STD	
CERT		45	ev. Jak	@ 4K	•	•	•	*	(0.08)	(0.25		· !.3) (1	0.5)	(0.08)	(0.27)	(2.4)	(3.5)	
eTD	(3.5)			@ UL	*	(0.95)	•		•	*	(2	2.6) (1	* 4.6)_	•	*_	(2.7)	(4.9)	
3.0	(12.5) 国家			3433	1 (0.11)	PORATIVE FAMILY 2		EVAPORATIVE FA			AMILY 3		EVAPORATI					
@ UL			ATIVE F			2-D	RL.	ORVR	3-D	2-D	R	L OF	VR	3-D	2-D	RL	ORVR	
_	3-D	2-				0.35	0.00	(0.04)	*	*	 		•	*	T .*		*	
CERT	0.25	0.2			0.65	0.85	0.05	0.20		*			-	*	•	<u> </u>		
STD	0.65	0.0	35 0.	0.20	0.65	0.00	5.55						+				45 Title	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: That the listed vehicle models are permitted intermediate in-use compliance standards pursuant to Title 40, Code of Federal Regulations (40 CFR), Section 1811-04(p).

BE IT FURTHER RESOLVED: That the listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order. This Executive Order hereby supersedes Executive Order A-006-1383 dated April 27, 2006.

Executed at El Monte, California on this

_ day of August 2006

Annette Hebert, Chief Mobile Source Operations Division