

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP				VEHICLE TYPE (PC=passenger car; LDT=light-duty MDV=medium-duty vehicle; LVW=k vehicle weight; ALVW=adjusted L	EXHAUST EMISSION STANDARD CATEGORY (LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV)			EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied patroleum gas)				
200	7	7HYXT02.0JW5				LDT1: 0 - 3750 pounds LVW a 6000 pounds GVW LDT2: 3751 - 5750 pounds L and < 6000 pounds GVW	.vw	L	EV II ULEV		120K / 150K	Gasoline (Tler 2 Unleaded)			
No.			APORATIVE No.			SPECIAL FEATU EMISSION CONTROL S					OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC				
1	7H	7HYXR0125PDJ		1 WU-TV		WU-TWC, TW	YC, TWC, HO2S(2), SFI, OBD (F)				AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed				
2		* 4		ŧ	2						AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo/super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board				
3		* :4		2	3	* ·									
4		* E		ž.	4		٠				diagnostic prefix 2=parallel (2) suffix=series				
EV/ No		EC S No.	ENGINE SIZE (L)			VEHICLE MAKES & MODELS		ICLES SUBJECT TO SFTP			ABBREVIATIONS:				
1		1 2.0			I	HYUNDAI: (LDT1) TUCSON (2WD)									
1	1 1		2.0			HYUNDAI: (LDT2) TUCSON (4WD)									
•		•	* * .		I				*						

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]) RAF = * AF = *	NMOG or	CH4=methane NMOG=non-CH4 organic gases NMHC=non-CH4 hydrocarbons CO=carbon monoxide NOx=oxides of nitrogen LHOHO=formaldehyde PM=particulate matter RAF=reactivity adjustment factor 2.3 b [g/test]=23 day diurnal-hot-soak R. [g/mi]=running loss ORVR [g/ga]allon dispensed]=on-board refuelling vapor recovery g=gram										
	STD STD C/LDT1 LDT2 0.043 0.055		NMOG CERT	NMHC CERT [g/ml]	NMHC STD [g/mi]	mg=millig		rmile K=1			F≃degrees Fahrenheit HCHO [mg/mi]			elemental federal test p		
			[g/mi]			CERT	STD	CERT			CERT	STD	CERT	STD	CERT	STD
150	The State of the S		0.024	*	0.040	0.4	1.7	0.01	0.0	5	0.1	8	_ •	*	0.01	0.07
	100	@ UL	0.028	+	0.055	0.6	2.1	0.01	0.0	7	0.1	11	*	*	0.01	0.09
编进	: 📥 @ 50°F & 4K		0.061	*	0.080	0.4	1.7	0.003	0.0	5	0.2	16	•	•	*	*
CO [@ 20			SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV)			Ox [g/mi] osite)	CO [g/mi] (composite)		NMHC+NOx {g/mi] [US06]			CO [g/mi] [U\$06]	NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]	
50			= @ UL (Tier		CERT	STD	CERT	STD	CERT	STD	CE	RT ST	CERT	STD	CERT	STD
CERT	1,1			SFTP 1	*	*	*	•	0.03	0.14	5.	0.8	0.01	0.20	0.8	2.7
STD	10.0			SFTP 2	*	*	*	•	*	*	•	* *	*	*	*	*
a III	Ē.	VAPOR	ATIVE FAN	IILY 1	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3				E,	EVAPORATIVE FAMILY 4			
@ UL	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	. ORVI	R 3-D	2-D	RL	ORVR
CERT	0.39	0.5	2 0.02	0.06	*	*	*	*	* 1	*	*	*	*	•	*	*
STD	0.65	8.0	5 0,05	0.20	*	*	* [1	•	*	•	*	*	*	*	*

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 4 day of June 2006.

Allen Lyons, Chief

Mobile Source Operations Division