EXECUTIVE ORDER A-314-0074
New Passenger Cars, Light-Duty Trucks
and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE (PC=passenger car; LDT=light-d MDV=medium-duty vehicle; LVV vehicle weight; ALVW=adjuste	STANE (LEV=I	AUST EMISSION DARD CATEGORY DOWN emission vehicle; LEV=ultra LEV; LEV=super ULEV)	Y	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)			
200		7KMXT02.0KW5			6000 pounds GVW LDT2: 3751 – 5750 pounds	1: 0 – 3750 pounds LVW and < 6000 pounds GVW T2: 3751 – 5750 pounds LVW and < 6000 pounds GVW				120K / 150K	Gasoline (Tier 2 Unleaded)		
No.		APORATIVE No.			SPECIAL FEA EMISSION CONTROL	TURES &	S (ECS)	le OC	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing TWC				
1	7KM	7KMXR0125PDK		1	WU-TWC, TWC, HO2S(2), SFI, OBD (F)					AFS/HAFS=air-fuel ratio sensor/heated AFS FGR=exhaust			
2		•		2		*		ga:	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		•		3		*		— ∣тв	☐ [18]= throttle body injection TC/SC=turbo /super charger				
4		•				*		dia	CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series				
EVA No		EC S No.	ENGINE SIZE (L)		VEHICLE MAKES & MODELS	VEHIC	CLES SUBJ DARDS AR	ECT TO SFTP E <u>UNDERLINED</u>	ABBF	ABBREVIATIONS:			
1		1 2.0			KIA: (LDT1) SPORTAGE (2WD)								
1		1	1 2.0		KIA: (LDT2) SPORTAGE (4WD)								
- *													

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/ml]			NMOG @ RAF = * CH4 RAF = *		NMOG or							on-CH4 hydro r RAF≃react					
PC/LD			NMOG CERT	NMHC CERT	NMHC STD	mg=millig	ram mi=	mile K=	1000 mil	es or	F=degrees	n bispensed Fahrenheit	=on-board :	refueling vap plemental fe	or recovery	/ q=gram	
			[g/mi]	[g/ml]	[g/mi]		CO [g/mi]		Ox [g/m	ii]	HCHO	[mg/mi]	PM [g/mi]		Hwy NOx [g/mi]		
0.04	3	0.055				CERT	STD	CER	T S	STD	CERT	STD	CERT	STD	CERT	STD	
	182. I	@ 50K	0.026	*	0.040	0.4	1.7	0.005	5 0	0.05	0.1	8	*	*	0.01	0.07	
	1111		0.031	*	0.055	0.6	2.1	0.01	0.07	.07	0.1	11	*	*	0.01	0.09	
2.000	@ 50	0°F & 4K	0.064	*	0.080	0.5	1.7	0.004	0	.05	0.2	16	*	*	*		
@ 20	CO [g/ml] @ 20°F & 50K		SFTP 1 = @ 4K (SULEV, ULEV, LEV) or 50K (Tier 1, TLEV) SFTP 2 = @ UL (Tier 1, TLEV)		NMHC+NOx [g/mi] CO [g/ (composite) (campo			NMHC+NOx [g/mi] [US06]						[g/mi] 2031			
50					CERT	STD	CERT	STD	CER	T S	TD C	ERT ST			CERT	STD	
CERT	1.1			SFTP 1	•	*	*	•	0.04	0).14	5.0 8.0	-		0.7	2.7	
STD	10.0			SFTP 2	*	*	*	*	*		•	* *	-	*	*	*	
@ UL			TIVE FAM	ILY 1	EVAPORATIVE FAMILY 2			2	EVAPORATIVE FAMILY 3				F	EVAPORATIVE FAMILY 4			
	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-	D R	L ORVE		2-D	RL	ORVR	
CERT	0.41	0.50	0.02	0.05	+	*	*	*	*	4			-	1		*	
STD	0.65	0.85	0.05	0.20	*	*	*	*	*	† •		*	+	-		*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 25 day of July 2006.

Annette Hebert, Chief

Mobile Source Operations Division