

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD! YEAI		TEST GROUP			MDV: veh	VEHICLE TYPE passenger car; LDT=light-duty =medium-duty vehicle; LVW=ld icle weight; ALVW=adjusted L	CATEGOR\ vehicle; T ULEV=ultra i	LEV= transitional LEV; LEV; SULEV=super ULE	lon (V)	EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL. TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)				
2007	7	7MTXT03.0G8G			LDT	: <6,000 pounds GVWR, 3 5750 pounds LVW		er Ultra Low Emissi le (LEV II SULEV)	on	150K /150K	Gasoline				
No.		EVAPORATIVE FAMILY (EVAF)				SPECIAL FEATI EMISSION CONTROL S	YSTE	VIS (ECS)	* □ not applicable	OC.	/TWC=oxidizing/3-way  = warm-up cat. O2S/F	cat. ADSTWC=adsorbing TWC IO2S=oxygen sensor/heated O2S			
1	7MTXR0135A2B			1		2WU-TWC, HCAD-TWC, T	WC, 2F OBD		AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas rectroulation ARVPAIR=secondary air injection/pulsed—AIR MFI/SFI= multiport fuel injection/sequential MFI TBI= throttle body injection TC/SC=turbo /super charger						
2		•					*								
3	•			3		•					CAC=charge air cooler OBD (F) / (P)=full /partial on-board				
4		*					*		Periodic Trap Oxidizer						
EVAF No.							BBREVIATIONS: /B/ = Buick /C/ = Chevrolet /CD/ = adillac /G/ = GMC /O/ = Oldsmobile /P/ = Pontiac								
1		1	3.0		Mitsubishi: Outlander										
*	*		*	*					•						
•		* *			•										

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]				@ RAF= * RAF = *	NMOG or													
CER.	ERT STD		NMOG NMHC		NMHC STD	mg=millig	diurnal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery g=gram mg=milligram ml=mile K=1000 miles F=degrees Fahrenheit SFTP=supplemental federal test procedure											
0.02	7 (	0.055	CERT	CERT	[g/mi]		CO [g/ml]		NOx [g/mi]		HCHO [mg/mi]		PM [g/ml]		Hwy NOx [g/ml]			
			[g/mi]	[g/mi]		CERT	STD	CER	r st	D   C	CERT	STD	CERT	STD	CERT	STD		
1	@ 50K		*	*	*	*	•	*	*		*   *		*	*	•	•		
	@UL		0.008	*	0.010	0.5	1.0	0.01	0.0	2	*	4.	*	٠	0.01	0.03		
	@ 50°F & 4K		0.017 *		0.020	0.3	1.0	0.005	0.0	2	*	8.	•	*	*	•		
CO [	g/ml] °F&	∰ LE	EV) or 50K	ULEV, ULEV, (Tier 1, TLEV)	NMHC+No (comp				NMHC+NOx [g/mi] [US06]			CO [g/mi] [US06]		NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	K	SFTP 2	≖ @ ∩r (π	er 1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CE	RT ST	D CER	T STD	CERT	STD		
CERT	2.4	Post.		SFTP@4K	•	+	*	*	0.01	0.25	2	.4 10.	5 0.02	0.27	2.2	3.5		
STD	12.5	133	100	SFTP 2	4	*	*	•	*	•		* *		*	*	*		
@ UL	E	VAPOR.	ATIVE FA	MILY 1	EVAPORATIVE FAMILY 2				EVAPORATIVE FAMILY 3				E	EVAPORATIVE FAMILY 4				
	3-D	2-0	RI	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L ORV	'R 3-D	2-D	RL	ORVR		
CERT	0.43	0.4	3 0.0	1 0.003	1	*	*	•	*	*	*	•	•	*	•	*		
STD	0.50	0.5	0.0	5 0.20	*	•	•	*	*	*	•	*	*	*	*			

**BE IT FURTHER RESOLVED**: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

**BE IT FURTHER RESOLVED:** The listed vehicle models are granted a 0.005 g/mi NMOG credit for all certification and inuse testing pursuant to 13 CCR Section 1961(a)(12) [direct ozone reduction]. The NMOG certification level above reflects application of the 0.005 g/mi NMOG credit. The listed vehicle models are granted a baseline partial zeroemission-vehicle (PZEV) allowance of 0.2 pursuant to 13 CCR Section 1962(c).

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this \_\_\_\_\_\_ day of August 2006.

1

Annette Hebert, Chief

Mobile Source Operations Division