TOYOTA MOTOR CORPORATION

EXECUTIVE ORDER A-014-0573 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for

MODE		TEST GROUP		VEHICLE TYPE PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle welght; ALVW=adjusted LVW)	Vehicle	EMISSION STANDA Y (LEV=low emiss TLEV= transitional LEV; LEV; SULEV=super ULE	ION EVAPORATIVE	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas;		
2007 7TYXT04.7A				LDT: 6,001-8,500 pounds GVW, 5751-8500 pounds ALVW	"LEVII" [Low Emission Vehick (LEV II LEV)		LPG=liquefied petroleum ga		
	<u>FAMILY</u>	AMILY (EVAF) TYXR0190A32		SPECIAL FEATURES EMISSION CONTROL SYSTEM 2WU-TWC,2TWC,2AFS,2	AS (ECS)	* = not applicable	OC/TWC=oxidizing/3-way WU= warm-up cat. O2S/H AFS/HAFS=akr-fuel catlo	Gasoline rcat. ADSTWC=adsorbing TW HO2S=oxygen sensor/heated O2		
3			3 4	•			AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=s: gas recirculation AiR/PAIR=secondary air injection/AIR MFUSFI= multiport fuel injection/sequential in TBI= throttle body injection TC/SC=turbo /super chicked air cooler OBD (F) / (P)=full /partial on Idagnostic prefix 2=parallal / 21 prefix 2=parall			
EVAF No. 1	ECS No.	ENGINI SIZE (L 4.7)	STAR	DARDS AR	EUNDERLINED 7	Periodic Trap Oxidizer BBREVIATIONS: /B/ = E	P =tull /partial on-boar Itel		
				<u>_</u>	oyota Land (Cruiser Wagon 4WD;	Lexus LX 470	Oldshipbile (P) = Pontiac		

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

E [g/m]	CH4 F	RAF= *	NMOG o	Coltrogen	HCHO-6	O-non-CH	4 organic	gas NM	HC=non-	plicable	rhon CO-				
	NMOG CERT	NMHC CERT	NMHC STD	mg=millig	ram mi	=mile K=	inning ios 1000 mile:	S ORVI	R fo/galio	n dispensed	=on-board r	en acus	Z/3 D (g/tes	t]=2/3 da	
0.055	[g/mi]	[g/mi]	[g/mi]		[31.111	N(ox (g/mi)		НСНО	[ma/mi]			CALT (BRE D	rocedure	
@ 50K	0.031		 		210	CER	T \$1	D	CERT	STD	CERT		Hwy No		
<u> </u>		<u> </u>	0.075	0.2	3.4	0.03	0.0	05	*	15		310		STD	
	0.036	•	0.090	0.3	42	0.02	-	. 	 -				0.01	0.07	
50°F & 4K	•	•	*	 	 	- 0.03	0.0	<u>"</u>		18.	*	• 7	0.01	0.09	
SFTP 1 =	@ 4K (SUL	EV, ULEV.	NMHC+N	Ox [a/mi]	(CO				*			•	•		
EN LEV	/) or 50K Mi	or 1 Tr EVA	(comp	osite)	(com	oosite)	[g/mi]	[US06		CO [g/mi] [US06]			CO	[g/mi]	
	De the s	FTP@4K	+		CERI	STD		STE	CE	RT STD				C03] STD	
		+		 +			0.02	0.60	9.	6 11.8	0.02	0.44		4.0	
EVAPORA	TIVE EAN:			_		L*_	*	*	1	-	*		 -		
			EVAPORATIV		E FAMILY 2		EVAPOR/		ATIVE FAMILY 2		-				
			3-D	2-D	RL	ORVR					EV			AMILY 4	
			_ • 🗆		•		 +		H KL	ORVR	3-D	2-D	RL	ORVE	
1.15	0.05	0.20	•	•	•		- +		-		*	•	*		
	0.055	STD NMOG CERT [g/ml] @ 50K 0.031 @ UL 0.036 60°F & 4K SFTP 1 = @ 4K (SUL LEV) or 50K (Till SFTP 2 = @ UL (Ther STP 2 =	STD NMOG CERT CERT [g/ml]	STD	O.055 CERT CERT STD CO CERT G/mi] G/mi] G/mi] G/mi] CO CERT CERT G/mi] CO CERT CERT G/mi] G/mi]	O.055	O.055 CERT CERT [g/mi] [g/mi] [g/mi] [g/mi]	O.055 CERT CERT G/mi] G/mi] G/mi] G/mi] G/mi] G/mi] CO [g/mi] NOX [g/mi] CERT STD CERT STD	O.055 CERT CERT G/mi] G/mi] G/mi] G/mi] G/mi] G/mi] CERT STD CERT STD CERT STD CERT STD CERT STD CERT STD O.056 O.090 O.3 4.2 O.03 O.05 O.090 O.3 4.2 O.03 O.07 O.090 O.3 O.090 O.090 O.3 O.090 O.09	O.055 CERT CERT G/mil G/mil G/mil G/mil G/mil G/mil CERT STD STD CERT STD STD	O.055 CERT CERT Gymi Gymi	O.055 CERT CERT Gert Gert	CERT CERT CERT CONTINUED CONTINU	NMOG CERT CERT CERT [g/mi] [g/mi] [g/mi] [g/mi] [g/mi] [g/mi] [g/mi] NOX [g/mi] NOX [g/mi] HCHO [mg/mi] PM [g/mi] PM [g/mi] HCHO [mg/mi] HCHO [mg/mi] PM [g/mi] HCHO [mg/mi] HCHO [mg/mi]	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.1 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

day of August 2006.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

Annette Hebert, Chief

Mobile Source Operations Division