

## **GENERAL MOTORS CORPORATION**

**EXECUTIVE ORDER A-006-1478-1** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL TEST GROU		VEHICLE TYPE	EXHAUST EMISSION STANDARD CATEGORY	USEFU (mil		IN- COMP ('=N/A or A/E=ex	MEDIATE USE LIANCE full In-use; h. / evap. late in-use)	FUEL TYPE	
2008	8GMXT06.2382	LDT: 6001-8500# GVW, 3751-	"LEV II" Low Emission Vehicle (LEV II LEV)	EXH / ORVR	EVAP	EXH	EVAP	Gasoline (Tier 2 Unleaded)	
		5750# ALVW	<u> </u>	150K 150K		•	•	· '	
No.		SPECIAL FEATURES	EVAPORATIVE						
1	2TWC, 2	8GMXR0	8GMXR0176820						
		8GMXR0	223840						
•		*	•			3.2			
•		*	•						

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### **BE IT FURTHER RESOLVED:**

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### **BE IT FURTHER RESOLVED:**

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-006-1478 dated March 28, 2007.

Annette Hebert, Chief

Mobile Source Operations Division

#### GENERAL MOTORS CORPORATION

EXECUTIVE ORDER A-006-1478-1

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles

# **ATTACHMENT**

# **EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS**

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

AVERAGE		NMOG ( CH4 R	2) RAF="  AF = "	NMOG or	NMOG or NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon moi NHOG or HCHO=formaldehyde; PM=particulate malter; RAF=reactivity adjustment factor; 2/3 D [g/test]=hot-soak; RL [g/mi]=running loss: ORVR [g/galion dispensed]⇒on-board reflueling vapor recove									=2/3 day diumal+				
CERT	STD	NMOG	NMHC	NMHC STD	not-soak; K	r (B/wi)=ւրստ	ning loss; OR	VR (g/gallon	: dispensed]=	on-board refi	ueling vapor r il test procedi	ecovery: g=q	ıram; <b>mg≃</b> milliç	gram				
0.047	0.050	CERT [g/mi]	CERT [g/ml]	[g/ml]	[00]	g/mi]	NOx	g/mi]	НСНО	[mg/ml]	PM	g/mi]	Hwy NO					
		<del></del>	10		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD				
30.	@ 50K	0.049	*	0.075	1.5	3.4	0.02	0.05	*	15.		•	0.02	0.07				
	@ UL	0,066	*	0.090	1.8	4.2	0.04	0.07	*	18.	*	0.01	0.04	0.09				
<b>111</b> 0	50°F & 4K		•	•	*	•	•	*	*	*		*	•					

	D [g/mi] D°F & 50K			Ox [g/mi] osite)	CO [	g/mi] oosite)		:+NOx [US08]	CO [	g/mi] 606]		+NOx [SC03]	] 00 08]	
(Q) 2(	) F & 50K	4.33	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD
CERT	4.8	SFTP @ 4000 miles	*	*	*	*	0.15	0.40	7.0	10.5	0.06	0.31	1.3	3.5
STD	12.5	SFTP @ * miles	•	*	*	•	+	•	*	•	*		*	•

Evaporative Family	3-Days Diurn: (grams/te		2-Days Diurn (grams/te	al + Hot Soak est) @ UL	Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
	CERT	STD	CERT	STD	CERT	\$TD	CERT	STD	
8GMXR0176820	0.48	0.90	0.35	1.15	0.00	0.05	0.03	0.20	
8GMXR0223840	0.71	0.90	0.65	1.15	0.00	0.05	0.03	0.20	
*	*	•	4	*	*	•	•		
*	+	*	*	*	* "	*			

<sup>\* =</sup> not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; ECS= Emission Control System; STD= Standard; CERT= Certification; LVW=loaded vehicle welght; ALVW=adjusted LVW; LEV=low emission vehicle; TLEV=transitional LEV; ULEV=ultra LEV; SULEV=super ULEV; TWC=3-way catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; OC=oxidizing catalyst; O2S=oxygen sensor; H02S=heated O2S; AFS/HAFS=air-fuel ratio sensor / heated AFS; EGR=exhaust gas recirculation; AIR=secondary air injection; PAIR=pulsed AIR; MFI= multiport fuel injection; SFI=sequential MFI; TBI=throttle body injection; TC/SC= turbo/super charger; CAC=charge air cooler, OBD (F)/(P)=full/partial on-board diagnostic; DOR=direct ozone reducing; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol Fuel

### 2008 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE FAMILY	ECS NO.	ENGINE SIZE (L)	IN- COMP (*=N/A or A/E=ex	MEDIATE USE LIANCE full in-use; h. / evap. late in-use)	PHASE-IN STD.	OBD II
					EXH	EVAP	]	
CADILLAC	ESCALADE EXT AWD	8GMXR0223840	1	6.2	•	•	SFTP	Full
CADILLAC	ESCALADE 2WD	8GMXR0176820	1	6.2	*	•	SFTP	Full
CADILLAC	ESCALADE AWD	8GMXR0176820	1	6.2	*	•	SFTP	Fuli
CADILLAC	ESCALADE ESV AWD	8GMXR0223840	1	6.2	*	•	SFTP	Full
GMC	C15 SIERRA 2WD	8GMXR0176820	1	6.2	. *	•	SFTP	Full
GMC	K15 SIERRA AWD	8GMXR0176820	1	6.2	*	•	SFTP	Full
GMC	K1500 YUKON DENALI AWD	8GMXR0176820	1	6.2	*	*	SFTP	Full
GMC	K1500 YUKON XL AWD	8GMXR0223840	1	6.2	*	*	SFTP	Full
CHEVROLET	C1500 TAHOE 2WD	8GMXR0176820	1	6.2	*		SFTP	Full
GMC	C1500 YUKON 2WD	8GMXR0176820	1	6.2	*	+	SFTP	Full
GMC	C1500 YUKON XL 2WD	8GMXR0223840	1	6.2	•	*	SFTP	Full
CADILLAC	ESCALADE ESV 2WD	BGMXR0223840	1	6.2	*		SFTP	Fuff