## **CHRYSLER LLC**

EXECUTIVE ORDER A-009-1036 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD YEA		TEST GROUP			VEHICLE TYPE {PC=passenger car; LDT=light-d MDV=medium-duty vehicle; LVV vehicle weight; ALVW=adjuste	STAND: {LEV=lo: UL	UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG≃compressed/ ilquefied natural gas; LPG=liquefied petroleum gas)				
200	9	9CRXJ02.4UP0			PC; LDT 0-3750 # LVW : < 6000 # GVW		SEPA BIN 4 ed as ARB LEV2 ULEV	120K / 150K	Gasoline				
No.		APORA MILY (E		No	SPECIAL FEA EMISSION CONTROL			* = not applicable	OC/TWC=oxidizing/3-way o	at. ADSTWC=adsorbing TWC 02S=oxygen sensor/heated 02S			
1	9CRXR0112PK0			1	TWC,	HO2S(2),	SFI, OBD (F)	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust					
2		* 2				+	***	AIR MFI/SFI= multiport	gas recirculation AIR/PAIR=secondary air injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI				
3		* 3				•		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board diagnostic prefix 2=parallel (2) suffix=series					
4		. 4											
EV/ No		EC S No.	SENGINE		VEHICLE MAKES & MODELS			ECT TO SFTP E <u>UNDERLINED</u>	ABBREVIATIONS:				
1		1	2.4		(PC) DODGE: CALIBER								
1		1 2.4			(LDT) JEEP: COMPASS 2WD, PATRIOT 2WD								
*		* ]	*					+					

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE STD [g/ml]		NMOG @ RAF = * CH4 RAF = *		NMOG or	diumal+hot-soak RL [g/mi]=running loss ORVR [g/gallon dispensed]=on-board refueling vapor recovery garram												
CER		STD	NMOG	NMHC	STD	mg=millig	ram mi	mile K=1	1900 miles	F=deg	rees Fa	ahrenheit	SFTP=supp	lemental fe	derai test pi	ocedure	
PC/LD			CERT		[g/mi]	CO [g/mi]		NOx [g/mi]		_   H	HCHO [m		PM [g	PM [g/mi]		Hwy NOx [g/mi]	
0.04		0.038	[g/ml]	[g/mi]		CERT	STD	CERT	r sti	D CE	RT	STD	CERT	STD	CERT	STD	
1 1		@ 50K	*	•	•	*		•	*		*	*	٠	*	•	*	
		@ UL	0.040	*	0.070	1.4	2.1	0.02	0.0	4	•	11	•	0.01	0.003	0.05	
:	@ 50	°F & 4K	*	•	•	*	*	*	•		*	*	*	•	*	*	
	CO [g/ml]   SFTP 1 = ( @ 20°F & LEV)			= @ 4K (SULEV, ULEV, V) or 50K (Tier 1, TLEV)				[g/mi] NMHC+N posite) [g/mi] [US					NMHC+NOx [g/mi] [SC03]		CO [g/mi] [SC03]		
50	К	SFTP 2	= @ UL (Tie	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	ÇE	RT ST			CERT	STD	
CERT	2.9	7	- 45	SFTP 1	+	*	•	*	0.01	0.14	1.	6 8.0	0.03	0.20	0.6	2.7	
STD	10.0	1.554		SFTP 2	0.04	0.65	*	*	*		4.	1 11.	1 *	*	2.6	3.7	
@ UL	EVAPORATIVE FAMILY 1				EVA	EVAPORATIVE FAMILY 2			EVAPORATIVE FAMILY 3			EVAPORATIVE FAMILY 4					
<u> </u>	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL	ORVR	
CERT	0.46	0.5	0.000	0.08	*	*	*	*	*	*	•	*	+	*	*	*	
STD	0.50	0.6	5 0.05	0.20	*	****	*	•	*	•	*	*	•	· ·	*	•	

**BE IT FURTHER RESOLVED**: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

## **CHRYSLER LLC**

EXECUTIVE ORDER A-009-1036 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The listed vehicle models are federally certified, and are certified under the provisions of 13 CCR Section 1961(a)(14) and the incorporated test procedures.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 27 day of May 2008.

Annette Hebert, Chief

Mobile Source Operations Division