

FUJI HEAVY INDUSTRIES, LTD.

EXECUTIVE ORDER A-002-0160-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MOD		TEST GROUP			VEHICLE TYPE {PC=passenger car; LDT=light-duty truck; MDV=medium-duty vehicle; LVW=loaded vehicle weight; ALVW=adjusted LVW}			UST EMISSION ARD CATEGORY w emission vehicle; EV=ultra LEV; EV=super ULEV)	EXHAUST & ORVR/ EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefled natural gas; LPG=liquefled petroleum gas)				
200		9FJXJ02.5MXG		G (PC and LDT ≤ 6,000 pounds (PC; LDT 3,751 – 5,750 pounds	LVW)	1	LEV II LEV	150K / 1 50K	Gasoline				
No.	EVAF FAMI			No.	SPECIAL FEATUREMISSION CONTROL S		S (ECS)	* = not applicable	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heate					
1	9FJX	9FJXR01253CJ			TWC(2), HAFS	, HO2S, S	SFI, EGR, O	AFS/HAFS=air-fuel ratio sensor/heated AFS_EGR=exhaust						
2	9FJX	FJXR01253CM				*		gas recirculation AIR/PAIR=secondary air Injection/pulsed AIR MFI/SFI= multiport fuel injection/sequential MFI						
3		*				*		TBI= throttle body injection TC/SC=turbo /super charger CAC=charge air cooler OBD (F) / (P)=full /partial on-board						
4		1		4		*		diagnostic prefix 2=parallel (2) suffix=series						
EVAI		CS	ENGIN		VEHICLE	VEHIC	CLES SUBJ	CT TO SETP						
No.	N	lo.	SIZE (L)	MAKES & MODELS	STANE	DARDS AR	UNDERLINED						
1	1 2.5			SUBARU: (PC) LEGACY AWD (2.51, 2.5i-Ltd.), LEGACY WAGON AWD 2.5i										
1		1 2.5			SUBARU: (LDT 3,751-5,750 pounds LWV) OUTBACK WAGON AWD (BASE, Ltd.)									
2	1 2.5			SUBARU: (PC) IMPREZA AWD 2.5I, IMPREZA WAGON AWD 2.5I, IMPREZA WAGON OUTBACK AWD 2.5I										
2	1 2		2.5		SUBARU: (LDT 3,751-5,750 pounds LVW) FORESTER 2.5X, FORESTER 2.5XS									

The exhaust and evaporative emission standards (STD) and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

	OG FLEI		NMOG @			CH4=metl	nane NMO	G⊭non-CH4	organic	gases N	IMHC=no	n-CH4 hydro	carbons C0	=carbon m	onoxide NC	x=oxides	
_	1444		CH4 R		NMOG or NMHC	diurnal+h	n H CHO≕ ot-soak R	formaldehy L [g/mi]=ru	rde PM≕; nninalos	particula s ORVF	te matter R fo/pallo	RAF=react n dispensed	livity adjustm]=on-board n	ent factor	2/3 D [g/test	j=2/3 day o≡oram	
			NMOG NMHC		STD	mg=millig	rem / ml=	mile K=	1000 mile:	s F=	degrees	Fahrenheit	SFTP=supp	lemental fed	derai test pr	ocedure	
PC/LD		T2	CERT	CERT	[g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [g/mi]		Hwy NOx [g/mi]		
0.03	3 0.0	047	[g/mi]	[g/mi]	13	CERT	STD	CER	T S	rd "	CERT	STD	CERT	STD	CERT	STD	
Sv∓ti	(0	9 50K	0.050	•	0.075	0.6	3.4	0.02	0.	05	1	15	*	•	0.01	0.07	
		@ UL	0.060		0.090	0.9	4.2	0.02	0.	07	1	18	*	0.01	0.01	0.09	
è	@ 50°F & 4K		0.121	•	0.150	1.1	3.4	0.01	0.	05	1	30	4	4	*	*	
	CO [g/mi] SFTP 1 = @ 4K (SULEV, ULEV, @ 20°F & LEV) or 50K (Rer 1, TLEV)					NMHC+NOx [g/mi] CO [g/mi] (composite) (composite)					CO [g/mi] [U\$06]		HC+NOx CO [g/mi] i] [SC03] [SC03]				
50	K	SF TP 2 =	@ UL (Tler	1, TLEV)	CERT	STD	CERT	STD	CERT	ST	D CI	RT ST	D CERT	STD	CERT	STD	
CERT	2.8			SFTP 1	*	*	*	*	0.03	0.1	4 2	2.9 8.	0.02	0.20	0.1	2.7	
STD	10.0	100	A.	SFTP 2	*	*	*	*	*	*		* *	*	•	+	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2				EV	EVAPORATIVE FAMILY 3				EVAPORATIVE FAMILY 4			
	3-D	2-0	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	R	L ORV	R 3-D	2-D	RL	ORVR	
CERT	0.24	0.33	0.00	0.02	0.15	0.19	0.00	0.01	*	*	,	*	*	*	*	•	
STD	0.50	0.65	0.05	0.20	0.50	0.65	0.05	0.20	*	*		*	*	*	ŧ	•	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: Additional NMOG fleet average or vehicle equivalent credits are granted to the listed vehicle models pursuant to 13 CCR Section 1961(a)(8) [optional 150K certification].



FUJI HEAVY INDUSTRIES, LTD.

EXECUTIVE ORDER A-002-0160-2 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified based on the manufacturer's reported emissions and attestation that it meets all applicable certification requirements currently in effect and enforceable for the 2009 model year, as described above. A January 16, 2007 Order currently enjoins the Executive Officer from enforcing any provision of California Health and Safety Code section 43018.5(b)(1) concerning certification to the requirements for 2009 and subsequent model passenger cars, light-duty trucks, and medium-duty vehicles adopted pursuant to AB 1493. (Document 606, Case No. 1:04-CV-06663-AWI-GSA, U.S. Dist. Ct. E. Dist. of CA (Fresno Div.).) If said injunction ceases to be in effect, the manufacturer will have 45 days from ARB notification to demonstrate compliance with AB 1493 requirements, including the determination of the greenhouse gas values for the test group listed in this Executive Order. Nothing in this Executive Order is intended to constitute enforcement of any requirement under AB 1493 for 2009 model year vehicles.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

This Executive Order hereby supersedes Executive Order A-002-0160-1 dated April 22, 2008.

Executed at El Monte, California on this

_ day of July 2008.

Annette Hebert, Chief

Mobile Source Operations Division