

## **AUDI AG**

EXECUTIVE ORDER A-030-0245 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515-39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED: That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR		TEST GROUP			VEHICLE TYPE  PC=passenger car; LDT=light-duty truck;  MDV=medium-duty vehicle; LVW=loaded  vehicle weight; GVW=gross VW)	STAND (LEV=low of transitions	AUST EMISSION DARD CATEGORY DARD CHECORY DESCRIPTION D		EXHAUST & ORVR / EVAPORATIVE USEFUL LIFE (UL) (miles)	FUEL TYPE (CNG/LNG=compressed/ liquefied natural gas; LPG=liquefied petroleum gas)					
201	2	CADXJ02.03UB		1	Passenger Car, DT: GVW< 6000 lbs 3751-5750 lbs LVW	"LEV II" Ultra Low Emission Vehicle (LEV II ULEV)			120K / 150K	Gasoline (Tier 2 Unleaded)					
No.		APORA MILY (E		No.	SPECIAL FEATURES & EMISSION CONTROL SYSTEM		* = not applicable	W	OC/TWC=oxidizing/3-way cat. ADSTWC=adsorbing WU= warm-up cat. O2S/HO2S=oxygen sensor/heated						
1	CAD	XR014	10B8Q	1	TWC, H02S(2), DGI,	TC, CAC, OF		#AFS/HAFS=air-fuel ratio sensor/heated AFS EGR=exhaust gas recirculation AIR/PAIR=secondary air injection/pulsed AIR/PAIR=secondary air injection/pulsed IAIR MFI/SFI= multiport fuel injection/sequential MFI TBI=1.3throttle body injection DGI=direct gasoline injection							
2	CAD	XR014	10C7A	2	*		A								
3		*			*		- ∰T¢	TC/SC=turbo /super charger CAC=charge air cooler OBD  (F) / (P)=full /partial on-board diagnostic prefix 2=parallel  (2) suffix=series							
4		•			*		(F (2								
EVAI No.		ECS No.	ENGINE SIZE (L)				ECT TO SFTP E UNDERLINED	ABB	REVIATIONS:						
1		1	2.0		(PC) Audi: A4, A4 quattro, A4 Avant quattro, A5 quattro, A5 Cabriolet, A5 Cabriolet quattro										
1		1	2.0		(LDT 3751-5750 lbs) <u>Audi Q5</u>										
2		1	2.0	T	(PC) Audi: A6										
*		*	*				*								

The exhaust and evaporative emission standards (STD), as requested by the manufacturer, and certification emission levels (CERT) for the listed vehicles are as follows (compliance with the 50 °F testing requirement (for TLEV, LEV, ULEV, SULEV) may have been met based on the manufacturer's submitted compliance plan in lieu of testing). Any debit in the manufacturer's "NMOG Fleet Average" (PC and LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required. (For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET AVERAGE [g/mi]			NMOG @ RAF= * CH4 RAF = *		NMOG or	nitrogen	HCHO≈for	maidehyde	PM=part	iculate ma	atter R/	λF≐reactiv	rbon CO=c rity adjustme =on-board r	ent factor	2/3 D [g/test	]=2/3 day	
PC ST	D LD1	STD			NMHC	mg=millig		mile K=1	000 miles	F=deg	rees Fah	renheit			deral test pr		
0.035	0	043	CERT	CERT	[g/mi]		CO [g/mi]		NOx [g/mi]		HCHO [mg/mi]		PM [c			Hwy NOx [g/mi]	
0.000		-	[g/mi]	[g/mi]		CERT	STD	CERT	STD	CE	RT	STD	CERT	STD	CERT	STD	
		@ 50K	0.028	*	0.040	0.9	1.7	0.02	0.05	<u> </u>	*	8	*	*	0.01	0.07	
		@ UL	0.036	*	0.055	1.1	2.1	0.03	0.07	<u>'</u>	*	11	*	0.01	0.02	0.09	
	@ 50°	F & 4K	0.064	*	0.080	1.0	1.7	0.03	0.05	;	*	16	*	*	*	*	
CO [ @ 20	g/mi] °F&	SFTP 1	= @ 4K (SUL V) or 50K (T	.EV, ULEV, ier 1, TLEV)	NMHC+NOx [g/mi] (composite)					+NOx [US06]		) [g/mi] US06]		HC+NOx i] [SC03]		[g/mi] C03]	
50		SFTP 2	= @ UL (Tier	1, TLEV)	CERT	STD	CERT	STD	CERT	STD	CER	TST	CER	STD	CERT	STD	
CERT	2.0	142	<i>Iniv</i> s	FTP @ 4K	*	. *		*	0.04	0.14	3.1	8.0	0.05	0.20	0.8	2.7	
STD	10.0		S S	FTP @ UL	*	*	•	*	*	*	•	*	*	*	*	*	
@ UL	EVAPORATIVE FAMILY 1				EVAPORATIVE FAMILY 2 EV				EVA	APORATIVE FAMILY 3			E	EVAPORATIVE FAMILY 4			
W 01	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORVR	3-D	2-D	RL	ORV	R 3-D	2-D	RL.	ORVR	
CERT	0.44	0.46	0.002	0.01	0.41	0.40	0.001	0.04	*	*	*	*	*	*	*	*	
STD	0.50	0.65	5 0.05	0.20	0.50	0.65	0.05	0.20	*	*	*	*	*	*	*	*	

BE IT FURTHER RESOLVED: That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED: The test group listed in this Executive Order is certified conditionally on the manufacturer providing test data to determine the greenhouse gas (GHG) emissions for the listed test group, expressed in grams per mile of carbon dioxide-equivalent (g/mi CO2-e), as required in section E.2.5.2 of the California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, as amended August 4, 2005 (the Test Procedures). Manufacturer shall provide the required data within 45 days after the date of the Executive Order unless (a) an extension is granted by the Executive Officer, or (b) the manufacturer demonstrates to the satisfaction of the Executive Officer that it is exempt from determining GHG emissions for the listed test group under section E.2.5.3 (Intermediate Volume Manufacturers) or E.2.5.4 (Small Volume Manufacturers) of the Test Procedures. Failure to comply with the certification requirement to determine the GHG emissions for the listed test group may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement therein, the manufacturer is not required to determine GHG emissions for any medium-duty vehicles in the listed test group that are not medium-duty passenger vehicles.



**AUDI AG** 

EXECUTIVE ORDER A-030-0245 New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations.

The Bureau of Automotive Repair will be notified by copy of this Executive Order.

174 day of February 2011. Executed at El Monte, California on this \_\_\_\_\_

Annette Hebert, Chief
Mobile Source Operations Division