**AUDI AG** 

**EXECUTIVE ORDER A-030-0270** 

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 2

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

#### IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

MODEL YEAR	TEST GROUP VEHICLE TYPE		EXHAUST EMISSION STANDARD CATEGORY	FE (miles)	FUEL TYPE			
2013	DADXJ02.0FUB	Passenger Car	"LEV II" Ultra Low Emission	EXH / ORVR	EVAP	Flexible Fuel: Ethanol (E85)/Gasoline (Tier		
			Vehicle (LEV II ULEV)	120K	150K	2 Unleaded)		
No.		CIAL FEATURES	EVAPORATIVE FAR		DISPLACEMENT (L)			
1	TWC, HO2S(2),	DFI, TC, CAC, OBD(P)	DADXR0140	DADXR0140B8F .				
•		*	•	·				
•								

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

#### BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50° Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG Fleet Average" (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

#### BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

#### **BE IT FURTHER RESOLVED:**

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this

30 day of August 2012.

Annette Hebert, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

## **ATTACHMENT**

# EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

NMOG FLEET NMOG @ RAF=* AVERAGE [g/mi] CH4 RAF = *		NMOG or	HCHO=form	naldehyde; I	M=particul	ete matter, Kr	/L=LBSC((A	diumal+ am; mg=milliq	oxides of nitrogen; al+ mg=milligram					
CERT	STD	NMOG CERT	NMHC CERT	STD	mi=mile; K=1000 miles; F CO [g/mi]		F=degrees	F=degrees Fahrenheit; SF NOx [g/mi]		plemental 190 10 [mg/mi]	al all test bloco	[g/ml]	Hwy NOx [g/	
0.024	0.035	[g/mi]	[g/mi]	[g/mi]	CERT	STD	CERT	STD	CER		CERT	STD	CERT	STD
	@ 50K	0.027	•	0.040 (0.075)	0.4 (0.7)	1.7	0.02 (0.04)	0.05 (0.05)	0.9	8. (8.)	*	*	0.01 (0.02)	0.07 (0.07
	@ UL	0.051 (0.029)	•	0.055	0.5 (1.1)	2.1 (2.1)	0.02 (0.07)	0.07 (0.07)	1.0 (*)	(11.)	(*)	(0.01)	(0.03)	(0.09
	50°F & 4K	<u> </u>	*	0.080	0.3	1.7	0.02	0.05	0.3	16.				
	į.			NMHC+No		CO [g (comp		NMHC+I [g/mi] [U		CO [g/n [US06		NHC+NOx mi] [SC03]		[g/ml] 203]
CO [ 60 20°F				CERT	STD	CERT	STD	CERT	STD	CERT	STD CEI	RT STD	CERT	STE

60°2′	)"r a oun	April 1831		CERT	STD	CERT	טופ	CERT	ייני ן	) OF					
		The Art of the State of the Sta				<del></del>		*	•	•	*	*	*	*	•
CERT	1.2	SFTP @ 4000 n	niles	*	*	*	*	(0.04)	(0.14)	(0.9)	(8.0)	(0.04)	(0.20)	(0.7)	(2.7)
-	(0.9) 10.0	SFTP@12		+	*	•	*	*	*	•	•	•		*	*
STD	(10.0)	n	niles				-	<u> </u>	<u>;                                    </u>					Definition 1	lanat
				urnal + Ho is/test) @ <sup>[</sup>		2-Days Di (gram	urnal + H s/test) @			tunning L ams/mile)		Red	covery (gr	Refueling \ ams/gallor	n) @ UL
\ <b>E</b>	Evaporative F	amily	(9										CERT		STD

	3-Days Diurna (grams/te	al + Hot Soak	2-Days Diurn (grams/te	al + Hot Soak est) @ UL	Runnin (grams/m		On-Board Refueling Vapor Recovery (grams/gallon) @ UL		
Evaporative Family	CERT	STD	CERT	STD	CERT	STD	CERT	0.20	
		0.50	0.39	0.65	0.010	0.05	0.02		
DADXR0140B8F	0.33	*	*	*	*	*	*	•	
				*	•	+	•	*	
*			<del></del>		•	•	*	*	
*	*	*	•		-		L D.T. COOCHOLAND		

### 2013 MODEL YEAR: VEHICLE MODELS INFORMATION

MAKE	MODEL	EVAPORATIVE E FAMILY		ENGINE SIZE (L)	VEHICLE TYPE	SPECIAL FEATURES	OBD II	
AUDI	A5 QUATTRO CABRIOLET	DADXR0140B8F	1	2	PC	•	Partial	
AUDI	A5 QUATTRO	DADXR0140B8F	1	2	PC	*	Partial	
AUDI	ALLROAD QUATTRO	DADXR0140B8F	1	2	PC	*	Partial	
AUDI	A4 QUATTRO	DADXR0140B8F	1	2	PC	*	Partial	