HONDA MOTOR CO., LTD.

EXECUTIVE ORDER A-023-0601

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 1 of 1

Pursuant to the authority vested in the Air Resources Board by Health and Safety Code (HSC), Div. 26, Part 5, Chap. 2; and pursuant to the authority vested in the undersigned by HSC Sections 39515 & 39516 and Executive Order G-02-003;

IT IS ORDERED AND RESOLVED:

That the following exhaust and evaporative emission control systems produced by the manufacturer are certified as described below. Production vehicles shall be in all material respects the same as those for which certification is granted.

		•	TEST	GROUF	INFORM	ATION						
MODEL YEAR	TEST GRO	UP VEHIC	LE CLASS(ES)		FUE	L CATEGORY		FL	JEL TYPE			
2014	EHNXV02.03H2 PC			PLUG-IN HYBRID ELECTRIC VEHICLE					ASOLINE			
	USEFUL LIF	E (miles)	VEHICLE	EMISSIC	N CATEG	ORY	in	ITERIM / INTERMS	EDIATE IN-USE STD			
EXH/	ORVR	EVAP	FTP			FTP		FTP	SFTP			
150	150,000 150,000		LEV3 SULEV2	0		LEV STAND- LONE	NN	/IOG+NOx	NMOG+NOx			
SPECIAL	EXHAUST EMISSION C	ONTROL SYSTEMS	en els Jaconia		OBD STATUS	MT BOW SON	ENGI	NE DISPLACEMENT (L)				
1 WU-TWC, TWC, WR-HO2S, HO2S, EGR, EGRC, SFI					ULL	•	111					
*					PARTIAL ALL MODE			2.0				
*	* *					×						
		E'	VAPORATIVE & REFUE	LING (E	VAP/ORVI	R) FAMILY INFOR	MATION	R.M. Variation and a facility of the second	And the second			
	EVAP / OF	RVR FAMILY	EVAPO	RATIVE	STD CAT	EGORY	Е	EVAP EMISSION STD VEHICLE CLASS				
	EHNXR	0186VGA		LEV3_OPTION 1					PC			
		+	-						*			
		*			*		*					
	er man y feet y to garden		EMISSI	ON CRE	DIT INFOR	MATION	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	<u> vitte til eg i og gregoria. Se til se t</u>				
	ALLOWANCE ST GROUP	AT PZEV ALLOWANCE FOR T GROUP	TZEV EST ALLOWANCE FO GROUP			G CREDIT FOR ZEV ZERO-EVAP	NMOG (REDIT FOR DOR	OPTIONAL EXH. STD FOR WORK TRUCKS			
ALL N	MODELS	ALL MODELS	ALL MODE	LS		N ·		N	N			
	e y magazine na enemala e		NMOG AND F	LEET A	VERAGE I	NFORMATION	The state of the s	····				
NMOG RAF	CH4 RAF	NMOG/NMHC RATIO	HCHO/NMHC RATIO			G+NOX FLEET LDT1 (0-3750 LVV	NMOG+NOX FLEET STD LDT2 (3751 LVW V) 8500 GVWR) + MDPV					
*	*	1.1	0.004093			0.107	•	0.128				

See the Attachment for Vehicle Models, Evaporative Family, Engine Displacement, Emission Control Systems, Phase-In Standards, OBD Compliance, Emission Standards and Certification Levels, and Abbreviations.

BE IT FURTHER RESOLVED:

That the exhaust and the evaporative emission standards and the certification emission levels for the listed vehicles are as listed on the Attachment. Compliance with the 50⁰ Fahrenheit testing requirement may have been met based on the manufacturer's submitted compliance plan in lieu of testing. Any debit in the manufacturer's "NMOG or NMOG+NOx Fleet Average" as applicable (PC or LDT) or "Vehicle Equivalent Credit" (MDV) compliance plan shall be equalized as required.

BE IT FURTHER RESOLVED:

That for the listed vehicle models, the manufacturer has attested to compliance with Title 13, California Code of Regulations, (13 CCR) Sections 1965 [emission control labels], 1968.2 [on-board diagnostic, full or partial compliance], 2035 et seq. [emission control warranty], 2235 [fuel tank fill pipes and openings] (gasoline and alcohol fueled vehicles only), and "High-Altitude Requirements" and "Inspection and Maintenance Emission Standards" (California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model PC, LDT and MDV).

BE IT FURTHER RESOLVED:

The test group listed in this Executive Order is certified conditionally on the manufacturer providing data to demonstrate compliance with California's greenhouse gas fleet average emission standard (CA GHG Standard) specified in Title 13, California Code of Regulations, (13 CCR) Section 1961.1 and the incorporated California Exhaust Emission Standards and Test Procedures for 2001 and Subsequent Model Passenger Cars, Light-Duty Trucks, and Medium-Duty Vehicles, amended March 29, 2010 (CA Test Procedures). The manufacturer has elected, under 13 CCR Section 1961.1(a)(1)(A)(ii) and under Section E.2.5.1(ii) of the CA Test Procedures, to demonstrate compliance with the CA GHG Standard by demonstrating compliance with the National greenhouse gas program (National GHG Program). Therefore, the test group listed in this Executive Order is certified conditionally further on the manufacturer complying with the

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 2 of 2

requirements specified in said provisions in 13 CCR, and Sections E.2.5.1(ii) and H.4.5(b) and H.4.5(c) of the CA Test Procedures (among other things, concerning data and information submission, timing, and format as specified by the Executive Officer). Failure to comply with the certification requirements to demonstrate compliance with CA GHG Standard by demonstrating compliance with the National GHG Program under said provisions in 13 CCR and CA Test Procedures may be cause for the Executive Officer to revoke the Executive Order. Vehicles in the revoked Executive Order shall be deemed uncertified and subject to penalties authorized under California law. Notwithstanding the requirement herein, a manufacturer that becomes, after MY2009, a large-volume manufacturer, as defined in 13 CCR Section 1900, is not required to comply with the CA GHG Standard until the beginning of the fourth model-year from becoming a large-volume manufacturer. Additionally, notwithstanding the requirement herein, a small-volume manufacturer, independent low-volume manufacturer, or intermediate volume-manufacturer, as defined in 13 CCR Section 1900, is not required to comply with CA GHG Standard during model-years (MY) 2012 through 2015.

BE IT FURTHER RESOLVED:

That the vehicles listed in this Executive Order are conditionally certified subject to the following. If within 90 days after the date of this conditional certification the manufacturer does not pass the confirmatory emissions testing conducted by the California Air Resources Board under the provisions of Title 40, Code of Federal Regulations, Section 86.1835-01(d) [conditional certification granted pending confirmatory testing by the agency] incorporated by reference in the "California 2015 and Subsequent Model Criteria Pollutant Exhaust Emission Standards And Test Procedures And 2017 And Subsequent Model Greenhouse Gas Exhaust Emission Standards And Test Procedures For Passenger Cars, Light-Duty Trucks, And Medium-Duty Vehicles", the conditional Executive Order shall become null and void ab initio. Any vehicles sold under the revoked conditional Executive Order shall be deemed uncertified and subject to a civil penalty of up to \$5000 per vehicle pursuant to Health and Safety Code Section 43154.

BE IT FURTHER RESOLVED:

Vehicles certified under this Executive Order shall not be introduced into commerce before January 2, 2013.

Vehicles certified under this Executive Order shall conform to all applicable California emission regulations. The Bureau of Automotive Repair will be notified by copy of this Executive Order.

Executed at El Monte, California on this 18

_ day of December 2012.

Annette Hebert, Chief

Mobile Source Operations Division

New Passenger Cars, Light-Duty Trucks and Medium-Duty Vehicles Page 3 of 3

⊘ Air Resources Board

ATTACHMENT

EXHAUST AND EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

(For bi-, dual- or flexible-fueled vehicles, the STD and CERT in parentheses are those applicable to testing on gasoline test fuel.)

EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS	(FTP	. HWFET	. 50 °F	. 20 ⁰ F1	ì
EXHAUST CHIBSION STANDANDS AND SENTIL ISATION ELTERS				,	

	FUEL TYPE	CH4=methane; NMOG=non-CH4 organic gas; NMHC=non-CH4 hydrocarbon; CO=carbon monoxide; NOx=oxides of nitrogen; HCHO=formaldehyde; PM=particulate matter; RAF=reactivity adjustment factor; 2/3 D [g/fest]=2/3 day diurnal+ hot-soak; RL [g/mi]=running loss; ORVR [g/gallon dispensed]=on-board refueling vapor recovery; g=gram; mg=milligram mi=mile; K=1000 miles; F=degrees Fahrenheit, SFTP=supplemental federal test procedure											
		NMOG+NOx (q/mi)		CO (CO (g/mi)		HCHO (mg/ml)		PM (g/mi)		HWY NMOG+NOx (g/mi)		
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD		
50°F @ 4K	E10-CARB	0.011	0.040	0.1	1.0	0.1	8	*	*	*	*		
@ UL	E10-CARB	0.011	0.020	0.2	1.0	0	4	*	0.01	0.007	0.020		
20°F @ 50K	GASOLINE-COLD CO HIGH OCTANE	+	*	0.4	10.0	*	*	* .	*	*	*		

SFTP EXHAUST EMISSION STANDARDS AND CERTIFICATION LEVELS

		US06 / UC (LA92)					SC03				COMPOSITE					
FUEL TYPE	NMOG+NOx (g/mi)		CO (g/ml) PM		PM (n	mg/ml) NMOG+NOx (g/ml)			CO (g/mi)		NMOG+NOx (g/mi)		CO (g/ml)			
		CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	CERT	STD	BIN	CERT	STD
@ UL	E10-CARB	0.01	0.05	0.1	9.6	*	÷	0.01	0.02	0.1	3.2	*	*	*	*	*

WHOLE VEHICLE EVAPORATIVE/ORVR EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE		S DIURNAL	+ HOT	VAPORATIVI 2-DAYS D		IG LOSS @ UL	ON-BOARD REFUELING VAPOR RECOVERY (g/gallon) @ UL			
		CERT	KK (g/test) @ STD	UL FEL	CERT	(g/test) @ UI STD	FEL	CERT	STD	CERT	STD
EHNXR0186VGA	GASOLINE - CA PHASE 2	0.337	0.350	*	0.290	0.350	*	0.00	0.05	0.05	0.20
*	*	*	*	*	•	*	*	*	*	*	*
*	*	*	*	*	*	*	*	*	*	*	*

FUEL ONLY & CANISTER BLEED EVAPORATIVE EMISSION STANDARDS AND CERTIFICATION LEVELS

EVAPORATIVE FAMILY	FUEL TYPE	ı	FUEL ONLY EVAP					
		3-DAYS DIURNA (g/test)		2-DAYS DIURN/ (g/test	AL + HOT SOAK) @ UL	CANISTER BLEED (g/test)		
		CERT	STD	CERT	STD	CERT	STD	
EHNXR0186VGA	GASOLINE - CA PHASE 2	0.0	0.0	0.0	0.0	*	*	
*	*	*	•	*	*	*	*	
**	ŧ .	*	*	*	*	*	*	

* =not applicable; UL=useful life; PC=passenger car; LDT=light-duty truck; LDT1=LDT<6000#GVWR,0-3750#LVW; LDT2=LDT<6000#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#LVW; LDT3=LDT 6001-8500#GVWR,3751-5750#LVW; LDT4=LDT 6001-8500#GVWR,5751-8500#ALVW; MDV=medium-duty vehicle; MDV4=MDV 8501-10000#GVWR; MDV5=MDV 10001-14000#GVWR; ECS= emission control system; STD= standard; CERT= certification; LVW=loaded vehicle weight; ALVW=adjusted LVW; LEV=low emission vehicle; ULEV=ultra LEV; SULEV=super ULEV; PZEV=partial allowance zero-emission vehicle; AT PZEV=advanced technology PZEV; TZEV=transitional zero-emission vehicle; TWC/OC=3-way/oxidizing catalyst; ADSTWC=adsorbing TWC; WU=warm-up catalyst; NAC=NOx adsorption catalyst; SCR-U or SCRC/SCR-N or SCRC-NH3= selective catalytic reduction-urea/ammonia; NH3OC=ammonia oxidation catalyst; CTOX/PTOX= continuous/periodic trap oxidizer; DPF = Diesel Particulate Filter (active); HO2S/O2S=heated/oxygen sensor; WR-HO2S or AFS=Wide rage/linear/heated air-fuel ratio sensor; NOXS= NOx sensor; RDQS=reductant quality sensor; NH3S = Ammonia sensor; EGR=exhaust gas recirculation; EGRC=EGR cooler; AIR/AIRE=secondary air injection (belt driven)/(electric driven); PAIR=pulsed AIR; SFI/MFI= sequentia/ multiport fuel injection; DFI=direct fuel injection; TC/SC= turbo/super charger; CAC=charge air cooler; OBD (F)/(P)(B)=full/partial/both on-board diagnostic; DOR=direct ozone reducing; HCT=Hydrocarbon Trap; BCAN=bleed carbon canister; prefix 2=parallel; (2) suffix=series; CNG/LNG= compressed/liquefied natural gas; LPG=liquefied petroleum gas; E85="85%" Ethanol (*15%"gasoline) Fuel; E10="10%" Ethanol (*90%"gasoline) Fuel

2014 MODEL YEAR: VEHICLE MODELS INFORMATION

	MAKE	MODEL	VEHICLE CLASS	ENGINE (L)	TRANSMISSION	EVAPORATIVE FAMILY	EXHAUST ECS	OBD	PZEV DESIGNA TION
-	HONDA	ACCORD PLUG-IN HYBRID	PC	2.0	CONTINUOUSLY VARIABLE	EHNXR0186VGA	1	PARTIAL	AT PZEV (TYPE F)

사용 사용 							
왕 과 경							
\$							
*							
1 4							
, , ,							
- f - 4							
√ - \$							
· •				•			
)							
1							
* 							
2* *							
1 4							
÷							
* *							
† √							
\(\frac{1}{\chi}\)							
Š.							
\$ \$							
j. Ž							
Š		•					
* * * * * * * * * * * * * * * * * * *	•						
* 						•	
\$ \$							
**************************************		•					
5. 7.							
46 - 10 - 10 - 10							
) (1)							
er Programmer Tr							
ŧ.							
Д 1							
11.0				•			
*							
T							
₹							