

**APPENDIX A-5**

**PROPOSED REGULATION ORDER**

**Zero Emission Vehicle Regulation: Electric Vehicle Charging Requirements**

**Title 13, California Code of Regulations**

This Page Left Intentionally Blank

**Appendix A-5**  
**PROPOSED REGULATION ORDER**

Amend and Renumber section 1962.2, title 13, California Code of Regulation (CCR), to read as follows:

[Note: Set forth below are the 2012 amendments to the electric vehicle charging requirements. The text of the amendments is shown in underline to indicate additions and ~~strikeout~~ to indicate deletions, compared to the preexisting regulatory language.]

**§ 1962.2.3.                    Electric Vehicle Charging Requirements**

(a) *Applicability.* This section applies to (1) all battery electric vehicles, range extended battery electric vehicles, except for model year 2006 through 2013 neighborhood electric vehicles, that qualify for ~~4.0 or greater~~ ZEV credit under section ~~1962.1 and 1962.2,~~ and (2) all hybrid electric vehicles that are capable of being recharged by a battery charger that transfers energy from the electricity grid to the vehicle for purposes of recharging the vehicle traction battery, ~~other than battery electric vehicles and hybrid electric vehicles that are only capable of Level 1 charging.~~

(b) *Definitions.*

(1) The definitions in section 1962.1 and 1962.2 apply to this section.

~~(2) "Level 1 charging" means a charging method that allows an electric vehicle or hybrid electric vehicle to be charged by having its charger connected to the most common grounded receptacle (NEMA 5-15R). A vehicle that is only capable of Level 1 charging is one that is charged by an on-board or off-board charger capable of accepting energy from the existing AC supply network. The maximum power is 12 amps, with a branch circuit rating of 15 amps, and continuous power of 1.44 kilowatts.~~

(c) *Requirements.*

(1) Beginning with the 2006 model year, all vehicles identified in subsection (a) must be equipped with a conductive charger inlet port and charging system which meets all the specifications applicable to AC Level 1 and Level 2 charging contained in Society of Automotive Engineers (SAE) Surface Vehicle Recommended Practice SAE J1772 REV NOV 2004 JAN2010, SAE Electric Vehicle and Plug in Hybrid Electric Vehicle Conductive Charge Coupler, which is incorporated herein by reference. All such vehicles must be equipped with an on-board charger with a minimum output of 3.3 kilovolt-amps-kilowatts, or, sufficient power to enable a complete charge in less than 4 hours.

Note: Authority cited: Sections 39600, 39601, 43013, 43018, 43101, 43104 and 43105, Health and Safety Code.  
Reference: Sections 39002, 39003, 39667, 43000, 43009.5, 43013, 43018, 43100, 43101, 43101.5, 43102, 43104, 43105, 43106, 43107, 43204 and 43205.5, Health and Safety Code. Authority cited: Sections 39600, 39601, 43013, 43018, 43101, 43104 and 43105, Health and Safety Code. Reference: Sections 38562, 39002, 39003, 39667, 43000, 43009.5, 43013, 43018, 43018.5, 43100, 43101, 43101.5, 43102, 43104, 43105, 43106, 43107, 43204 and 43205.5, Health and Safety Code.

§1962.3  
A-5-2

Date of Release: December 7, 2011  
Scheduled for Consideration: January 26-27, 2012